



arrere.

Blade width:

2.000 - 2.300 mm



Snow tank volume:

**3,0 m³** (compr. 3,6 m³)



Water tank volume:

1.000 I



Ice fields up to

1.800 m<sup>2</sup>



## **TECHNICAL DATA**

WEIGHT EMPTY/FULL (Standard) 5.350 kg / 6.350 kg

WHEELS 225 / 75 / R16

SPEED 0-13 kph

MOTOR 5 asynchronous electric motors

BATTERY 80 V 875 Ah low-maintenance

(incl. battery charger)



- 4,3" COLOUR DISPLAY WITH TOUCHSCREEN
- DIGITAL INDICATOR OF THE HYDRAULICALLY
  AD JUSTABLE CUTTING DEPTH
- CAN-BUS SYSTEM
- USB-INTERFACE
- AUTOM. MAINTENANCE INDICATOR
- DIGITAL WATER LEVEL INDICATOR
- ADJUSTABLE DRIVER'S SEAT WITH SUSPENSION AND ARMREST
- HYDRAULIC LEVER CONTROLS FOR WORK FUNCTIONS
- SIDE MIRRORS
- TOW HOOK
- LED ROTATING BEACON LIGHT
- 4 LED HEADLIGHTS AND 2 REARLIGHTS
- LED SNOW TANK LIGHT
- SERVO ASSISTED UNIT FOR OIL BATH BRAKE



- POWDER-COATED STAINLESS CONDITIONER
- 2 BLADES OF HIGH ALLOY STEEL (45-60 WORKING HOURS)
- 2 WIPING CLOTHS
- FAST BLADE CHANGE SYSTEM
- AUGER WASH SYSTEM
- ICE BOOST SNOW BREAKER FOR AUGERS
- MANUALLY ADJUSTABLE WATERFLOW
  - HYDRAULIC SAFETY HAND PUMP
  - SAFETY SWITCH FOR CONDITIONER AND SNOW TANK
  - HYDRAULICALLY POWERED SIDEBRUSH
  - AUTOMATIC WATER FILL AND STOP
  - STEEL SNOW TANK

2.150 mm - 2.420 mm



## Engo GmbH | S.r.l.

Forchstraße 9 / Via Forch 9 39040 Vahrn / Varna (BZ) · Italien / Italy T +39 0472 546 157

info@engo-ice.com www.engo-ice.com











This brochure has been prepared only as a general guide for the customer. Some equipment described or shown may be optional at  $% \left( 1\right) =\left( 1\right) \left( 1$ additional cost. Specifications are subject to change. For current product information, please contact the engo Company.

STATUS: 2023/2024

CERTIFICATION

MEMBER

MEMBER OF THE TECHNOALPIN GROUP









